

## TECHNICAL INFORMATION

### Cleentek 20

#### Special degreasing compound

<b>Description / Characteristics:</b>	<p><b>Cleentek 20</b> is an alkaline degreaser mostly used by spraying applications.  <b>Cleentek 20</b> can also be used by immersion at lower temperatures.  <b>Cleentek 20</b> will be used to remove heavy grease from bearings and as well as universal cleaner in repair shops to refurbish used parts like motors, gearboxes etc.</p> <ul style="list-style-type: none"> <li>➤ <b>Demulsifying</b></li> <li>➤ <b>very good cleaning performance</b></li> <li>➤ <b>universal applicable</b></li> <li>➤ <b>free of complexing agents like EDTA or NTA</b></li> </ul>									
<b>Suitable for:</b>	Stainless steel, ferrous metals, copper and its alloys Aluminium with limitations									
<b>Type of installation:</b>	Spraying, immersion, ultrasonic.									
<b>Application:</b>	<table style="width: 100%; border: none;"> <tr> <td style="width: 30%;"></td> <td style="width: 35%; text-align: center;">Spraying:</td> <td style="width: 35%; text-align: center;">Immersion:</td> </tr> <tr> <td>Koncentration:</td> <td style="text-align: center;">2 – 5 % v/v</td> <td style="text-align: center;">4 – 8 % v/v</td> </tr> <tr> <td>Temperatur:</td> <td style="text-align: center;">55 - 75° C</td> <td style="text-align: center;">20 - 55° C</td> </tr> </table> <p>Pretest alkali-sensitive materials, e.g. polished aluminium, at a hidden spot for material compatibility and treat such materials with lower concentrations.</p>		Spraying:	Immersion:	Koncentration:	2 – 5 % v/v	4 – 8 % v/v	Temperatur:	55 - 75° C	20 - 55° C
	Spraying:	Immersion:								
Koncentration:	2 – 5 % v/v	4 – 8 % v/v								
Temperatur:	55 - 75° C	20 - 55° C								
<b>Technical data:</b>	<table style="width: 100%; border: none;"> <tr> <td style="width: 30%;">Appearance:</td> <td style="width: 35%;">light yellow liquid</td> <td style="width: 35%;"></td> </tr> <tr> <td>Density:</td> <td>approx. 1.12 g/cm<sup>3</sup> (1 kg <math>\pm</math> 0.89 l)</td> <td></td> </tr> <tr> <td>pH-value (10 g/l):</td> <td>approx. 10.7</td> <td></td> </tr> </table>	Appearance:	light yellow liquid		Density:	approx. 1.12 g/cm <sup>3</sup> (1 kg $\pm$ 0.89 l)		pH-value (10 g/l):	approx. 10.7	
Appearance:	light yellow liquid									
Density:	approx. 1.12 g/cm <sup>3</sup> (1 kg $\pm$ 0.89 l)									
pH-value (10 g/l):	approx. 10.7									
<b>Major ingredients:</b>	Phosphates, silicates, amines, neutralised organic acids, surfactants									
<b>Determination of concentration:</b>	50 ml of bath solution are titrated with hydrochloric acid (0.5 mol/l) until you are reaching pH 7.0. Used ml hydrochloric acid x 0.45 = % v/v <b>Cleentek 20</b>									

When using these products, all applicable safety regulations for the use of chemicals must be observed. For storage information, danger specifications and safety regulations, please refer to the applicable safety data sheets. Application solutions and product remnants must be discarded in compliance with official regulations. The information given reflects our previous experience. With regard to varying operational conditions, this information is noncommittal and to be used as advice only. Therefore, we assume no liability whatsoever, including claims from third parties.